

Introducing ProCair
by Novis – alternating
solutions for the prevention and
treatment of pressure injuries and other
preventable complications of immobility.

	Standard size	King Single Size
CODE	APMPC-R03	APMPC-R03K
CAPACITY (SAFE WORKING LOAD)	30 - 200 kg	
SYSTEM ALTERNATION	1 in 2	
WARRANTY	3 year	
CARRY BAG	Carry bag with shoulder strap	
COMPLIANCE	IEC 60601-1, IEC60601-1-2, IEC60601-1-11	
ARTG	289458	
CARTON DIMENSIONS (L x W x H) in mm	100 x 670 x 270 mm	1150 x 670 x 300 mm
DIMENSIONS (L x W x H) in mm	2000 x 900 x 180 mm	2000 x 1050 x 1800 mm
MATTRESS WEIGHT	12 kg	13 kg
WEIGHT SENSOR PAD	No	
CPR TYPE	QuickTwist CPR at head end	
CELLS	NUMBER	21
	STATIC HEAD CELLS / ZONE	3
	NARROW FOOT CELLS / ZONE	4
	CELL FOAM INSERT MATERIAL	High resilience PU
	CELL MATERIAL	TPU laminated nylon
	MATTRESS AIR SUPPLY LINE	PVC air manifold and CPC quick release connectors
TOP COVER	MATERIAL / TYPE	Dark blue, polyurethane-laminated nylon - water resistant, vapour permeable multi-stretch
	FIRE RETARDANCY RATE	BS7175 Crib 5
	MAXIMUM WASH TEMPERATURE	95° C
	ATTACHEMENT	Dual zippers
	SEAM CONSTRUCTION	RF welded on all external seams
BASE	MATERIAL / TYPE	Black polyester
	HINGE	No
	FIXING STRAPS	Webbing at 4 corners, 2 at middle

General

Support
Surface

Control
Unit

POWER		110 - 220V 50/60Hz
COMPRESSORS		Single
OPERATION		Full digital control
CYCLE TIME		12 minutes
NOISE LEVEL, WITHIN 2 METERS		28db(A) ± 3
MIN / MAX PRESSURE		20-60mm HG +/- 6mm HG
ELECTRICAL PROTECTION TYPE		Class II Type BF
OPERATING ENVIRONMENT		Operation 15°C to 35°C Storage 5°C to 60°C
PRESSURE SETTING	AUTOMATIC	Yes – cyclical
	MANUAL	5 levels
CAIRALERT PATIENT EXIT ALARM		No
FOWLER FUNCTION		No Yes, Manual
BACKUP BATTERY		No
ALARMS		Low Pressure Power Failure



THERAPEUTIC DEVICES SHOULD ONLY BE USED IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS AND UNDER THE CONSENT, SUPERVISION AND MANAGEMENT OF A SUITABLY QUALIFIED HEALTH PROFESSIONAL.